

METHODS OF FORMING COATINGS ON GAS-DISPERSION FIXTURES IN CHEMICAL-VAPOR-DEPOSITION SYSTEMS

Technical Field

- 5 The present invention concerns methods of making integrated circuits, particularly layer-formation methods, such as chemical vapor deposition.

Background of the Invention

- Integrated circuits, the key components in thousands of electronic and
10 computer products, are interconnected networks of electrical components fabricated on a common foundation, or substrate. Fabricators generally build the circuits layer by layer, using techniques, such as deposition, doping, masking, and etching, to form thousands and even millions of microscopic resistors, transistors, and other electrical components on a silicon substrate, known as a wafer. The components are
15 then wired, or interconnected, together to define a specific electric circuit, such as a computer memory.

- One common technique for forming layers in an integrated circuit is called chemical vapor deposition. Chemical vapor deposition, or CVD, generally entails placing a substrate in a reaction chamber, introducing one or more gases, known as
20 precursor gases, into the chamber, and heating the substrate to prescribed temperatures. The precursor gases enters the chamber through a gas-dispersion fixture, such as a gas ring or a showerhead, one or more centimeters above the substrate, and descend toward the heated substrate. The gases react with each other and/or the heated substrate, blanketing its surface with a layer of material having a
25 composition based on the gases.

- Because of demands for smaller and smaller integrated circuits, it has become increasingly important that layers, such as those made using chemical vapor deposition, have uniform thickness across the substrate. One method of promoting uniform thickness in chemical vapor depositions is to coat the gas-dispersion fixture
30 with a uniform layer of the material before using the fixture in an actual deposition

on a substrate. This method is generally known as conditioning. Conventional conditioning techniques entail running the CVD chamber through several normal deposition cycles (that is, at normal temperatures and pressures) on a test or dummy substrate before using it for actual fabrication.

However, this conventional conditioning technique suffers from at least three problems. First, this technique produces coatings of poor thickness uniformity across gas-dispersion fixtures. In operation, these unevenly coated fixtures disperse gas unevenly and produce uneven depositions. Second, for large fabrication plants with many ideally identical CVD chambers, the coatings vary significantly from fixture to fixture, making it difficult for the CVD chambers to deposit layers of consistent quality. And third, the conventional technique yields coatings that adhere poorly to the gas-dispersion fixtures. Particles from poorly adherent coatings sometimes fall from fixtures onto underlying substrates, causing defects in integrated circuits.

Accordingly, there is a need for better ways of coating or conditioning gas-dispersion fixtures to promote uniform chemical vapor deposition and/or to reduce defects in integrated circuits.

Summary of the Invention

To address these and other problems, the present inventors devised new procedures for conditioning gas-dispersion fixtures in chemical-vapor-deposition (CVD) chambers. One conditioning procedure, in accord with the invention, entails heating at least a portion of a gas-dispersion fixture, such as a showerhead, to a temperature greater than its temperature during normal deposition operations and then passing one or more gases through the fixture to form a coating on it. Exemplary methods for raising the fixture temperature beyond its normal level include placing the fixture closer to a heated substrate holder than its normal operating position and/or introducing high-powered plasma in the vicinity of the fixture.

Increasing the temperature of the fixture during conditioning promotes uniform coating thickness and coating adhesion to the fixture. These in turn promote uniform chemical vapor depositions and reduce the likelihood of coating particles falling onto underlying substrates and causing integrated-circuit defects.

- Other aspects of the invention include conditioning a gas-dispersion fixture
5 at a higher-than-normal temperature, reducing the gas-dispersion fixture temperature, and then using the gas-dispersion fixture at the reduced temperature to form a layer of an integrated circuit.

Brief Description of the Drawings

- 10 Figure 1 is a simplified cross-sectional diagram of an exemplary chemical-vapor-deposition system 100; and
Figure 2 is a flow chart of an exemplary method of an exemplary method of operating system 100.

Description of the Preferred Embodiments

- 15 The following detailed description, which references and incorporates Figure 1 and 2, describes and illustrates specific embodiments of the invention. These embodiments, offered not to limit but only to exemplify and teach the invention, are shown and described in sufficient detail to enable those skilled in the art to practice
20 the invention. Thus, where appropriate to avoid obscuring the invention, the description may omit certain information known to those of skill in the art.

- Figure 1 is a simple sectional diagram of an exemplary chemical-vapor-deposition (CVD) system 100. System 100 includes a chamber 110, gas sourcing system 120, plasma source 130, and a exhaust system 140. Chamber 110 includes a
25 gas-dispersion fixture (or more generally apparatus) 112, a heated substrate holder (susceptor) 116. Gas-dispersion fixture 112, which includes a dispersion surface 113 that comprises holes, or apertures, 114, disperses one or more gases from gas sources 120 toward a substrate (wafer or integrated-circuit assembly) 150 on substrate holder 114. (As used herein, the term "substrate" encompasses a

semiconductor wafer as well as structures having one or more insulative, semi-insulative, conductive, or semiconductive layers and materials. Thus, for example, the term embraces silicon-on-insulator, silicon-on-sapphire, and other advanced structures.) Plasma source 130 introduces high-frequency electromagnetic energy into chamber 110 to facilitate reactions within the chamber.

5 The exemplary embodiment uses a commercial CVD chamber which provides a gas-dispersion fixture in the form of a showerhead. However, the invention is not limited to any particular chamber geometry or structure or gas-dispersion fixture geometry or structure. Indeed, it is believed that the invention is applicable to any CVD system having a gas-dispersion fixture. Thus, for example,
10 other embodiments use horizontal CVD systems, low- and high-pressure CVD systems, and hot- and cold-wall CVD systems.

Figure 2 includes a flow chart 200 that shows two exemplary operating modes for system 100. Flow chart 200 includes process blocks 202-216, with blocks 202-212 illustrating an exemplary fixture-conditioning mode 200a and
15 blocks 212-216 illustrating an exemplary normal-deposition mode 200b.

As block 202 shows, fixture-conditioning operating mode 202a begins with a user or wafer-transport system (not shown) placing or mounting a dummy substrate 150 onto substrate holder 116. Execution of the exemplary operating mode then proceeds to block 204.

20 In block 204, system 100 heats dispersion surface 113 to a conditioning temperature which is greater than a deposition temperature in normal-deposition mode 200b. The exemplary embodiment heats dispersion surface 113 to a conditioning temperature at least 5-10% greater than that conventionally used for deposition of Ti-Al-Cl-N on dispersion surface 113. However, for many other
25 compositions, the inventor expects that the conditioning temperature to be about 10-15%, 15-20%, 20-25%, 25-30%, 30-35%, 35-40%, 40-45%, 45-50% greater than the normal deposition temperature. It is believed that the teachings of this document will enable one of ordinary skill in the art to ascertain, without undue experimentation, an effective conditioning temperature or range of such

temperatures for any material composition that can be deposited through chemical vapor deposition.

In the exemplary embodiment, the desired conditioning temperature is established by moving substrate holder 116 to a distance less than one centimeter, for example 300 mils, from dispersion surface 113 and then controlling a heater in the substrate holder. Figure 1 shows this position as a fixture-conditioning position 116a.

Some other embodiments use other methods of heating dispersion surface 113 to a higher-than-normal temperature. For example, some embodiments move the dispersion surface closer to the substrate holder, and other embodiments use heat sources external to substrate holder, such as incandescent lighting or a heater internal to or attached to the gas-dispersion fixture. Thus, the invention is not limited to any particular method or structure for heating the dispersion surface to the conditioning temperature.

After establishing a desired conditioning temperature, execution proceeds to block 206, which entails introducing one or more gases to form material layer 115 on dispersion surface 113. The exemplary embodiment conventionally forms a titanium-aluminum-chlorine-nitrogen (Ti-Al-Cl-N) layer.

Block 208 shows that system 100 also operates plasma source 140 to introduce a plasma into chamber 110 to further facilitate formation of material layer 115. The exemplary embodiment introduces plasma power in excess of 400 Watts to further heat dispersion surface 113, thereby further enhancing properties of the resultant layer on the dispersion surface.

Block 210 entails stopping formation of material layer 115 and removing dummy substrate 150. Dummy substrate 150 can be discarded or reused for reconditioning fixture 112 or another fixture using the exemplary method or another incorporating teachings of the present invention.

In block 212, system 100 reduces the temperature of dispersion surface 113. In the exemplary embodiment, this entails moving substrate holder 116 to normal-deposition position 116b and/or curtailing or ending the introduction of plasma.

Other embodiments reduce the temperature through control of heaters external to substrate holder 116.

Next as block 214 shows, a target substrate is placed or mounted on substrate holder 116. The exemplary embodiment places the substrate manually or automatically on the substrate holder. For convenience, Figure 1 shows the target
5 substrate as substrate 150.

Block 216 entails forming or depositing a material layer 152 on a target substrate, such as substrate 150. In the exemplary embodiment, this entails introducing one or more gases and/or a plasma to form a Ti-Al-Cl-N layer, which is the same composition as that on layer 115 on dispersion surface 113. However,
10 there may be instances where a material layer of different composition than that on the gas-dispersion fixture is desirable.

After completion of this layer, other methods and materials can be used on substrate 150 to form a complete integrated circuit, such as a computer processor or memory circuit.
15

Conclusion

In furtherance of the art, the inventor has presented new procedures for conditioning gas-dispersion fixtures in chemical-vapor-deposition chambers. One exemplary procedure, in accord with the invention, entails heating at least a portion
20 of a gas-dispersion fixture, such as a showerhead, to a temperature greater than its temperature during normal deposition operations and then passing one or more gases through the fixture to form a coating on it. The high conditioning temperature promotes uniform coating thickness and coating adhesion to the fixture. These in turn promote uniform chemical vapor depositions and reduce the likelihood of
25 coating particles falling onto underlying substrates and causing integrated-circuit defects.

The embodiments described above are intended only to illustrate and teach one or more ways of practicing or implementing the present invention, not to restrict its breadth or scope. The scope of the invention intended to encompass all ways of

1907	1908	1909	1910	1911	1912	1913	1914	1915	1916	1917	1918	1919	1920	1921	1922	1923	1924	1925	1926	1927	1928	1929	1930	1931	1932	1933	1934	1935	1936	1937	1938	1939	1940	1941	1942	1943	1944	1945	1946	1947	1948	1949	1950	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------